


PRECISION ACCRETECH BLADE ULTRA HARD METAL SAWS

 **ACCRETECH**
TOKYO SEIMITSU




**Ultra-hard metal saw that does not allow
burring on the edge through the cutting of
the variety of metal substrate.
It can be the total solution for cutting that
can respond to the new demands.**

- Cutting blade for metal substrate
- Perfect for metals and resins:
- Restrains burring and enables sharp cutting



■ Processing example Ultra-hard metal saw



■ Aluminum substrate cutting

With conventional diamond blade
metal burring-less cutting was
impossible.
The ultra-hard metal saw can
realize metal burring-less cutting.


 **ACCRETECH**

TOKYO SEIMITSU



■ Dimension

	56D	0.1T	40H	
O.D.		Blade thickness		I.D.
Standard Dimension	O.D. (mm)	Blade thickness (mm)	I.D. (mm)	
Availability size	2",3"	0.08 to 0.3	± 0.01	40
Tolerance	+ 0.2 - 0			+0.016 -0



■ Material

Material	JIS K10 (or similar materials)	
Hardness	92.0 HRA	
Transverse rupture strength	3.2 Gpa	
Fracture toughness	6.8 Mpa·m ^{1/2}	
Density	14.9g /cm ³	

■ Ordering the product

When ordering our product, please refer to our catalog and let us know the details of the product as below.

- 1) Shape and size/ Detailed blade shape and precision.
- 2) Specifications/ Desired specification as well as the current in-use blade.
- 3) Cutting work and condition/ Machine in use, RPM, feed speed, coolant flow rate.

■ Precautions

In order to use the product safely and to bring out the best of the blade's performance, please make sure to thoroughly read the specifications and other related materials of the product.

* The catalog is subject to change without notice.

* The catalog is not to guarantee the product quality.

Tokyo Seimitsu Co., Ltd.

2968-2, Ishikawa-machi, Hachioji-city, Tokyo 192-0032, Japan TEL.+81(42)642-0390 FAX.+81(42)642-0484

<http://www.accretech.jp>